SOLENOID VALVES

2/2 PILOT OPERATED- DIAPHRAGM SERIES

TYPE: SS 221 W-NORMALLY CLOSED

FOR WATER/OIL

Application

These valves are specially designed for domestic/ irrigation/ agriculture and industrial application. Needs no maintenance due to durable body material made of brass. Highly reliable, long-life.

Airmatic



Port Size Model no.	Orifice in mm	Maximum working pressure (Kg/cm²)	Maximum working temperature Range of Fluid ^⁰ C	Flow Value m ⁷ /hr
---------------------	---------------------	--------------------------------------	---	----------------------------------

MODEL: SS-221 W-NORMAL CLOSED

Plastic Body/ Pipe Mounting

G 1/2	SS-221-W-04	16			4.8
G 3/4	SS-221-W-06	20	0 - 7	5 - 80°C	7.6
G 1	SS-221-W-08	25			12
G 11/4	SS-221-W-10	35			24
G 11/2	SS-221-W-12	40			29
G 2	SS-221-W-16	50			48

Material Specification

Body	Nylon		
Armature	St. Steel		
Seat	NBR		


Technical Specifications

Actuator Solenoid coil

Features

- * Quick Response
- * Stable
- * Long Life

Model Ordering Code Instruction




ORDER CODE: SS-221-W-06-010-B-N-AF-PWB-230VAC

Dimensions

TYPE: SS 221W

SIZE	DIMENSION				
	A	60	\bigcirc		
3/8 BSP	93	56	106	69	
1/2 BSP	93	56	106	69	
3/4 BSP	100	55	117	73	
1 BSP	104	78	125	99	
1 1/4 BSP	141	93	172	124	
1 1/2 BSP	141	93	172	124	
2 BSP	157	124	195	172	



DIMENSIONS ARE IN MM

Shah Pneumatics

Regd. Office: 28-30, Navketan Industrial Estate,

Mahakali Caves Road, Andheri (East),

Mumbai - 400 093, INDIA.

Phone: +91-22-6695 1090-94 Fax: +91-22-2687 5317

E-mail: shahpneu@bom3.vsnl.net.in Website: www.shah-pneumatics.com